



15740 W. 108th Street
Lenexa, KS 66219
1-913-888-0882

Instructions for proper application of



LEVELCOAT™ will not fill, level or straighten uneven joints or significant surface imperfections, however, it will provide a smooth, even finish comparable to skim coating the wall. **To maintain the proper viscosity, we recommend that ready-mixed LEVELCOAT™ be stirred to insure that any separation that may have taken place during shipping or storage doesn't interfere with a smooth, trouble-free spray-on application. Best results can be obtained by using a 1/2" drill with a paddle suitable for mixing joint compound. We recommend that the blade be kept fully immersed in the product while stirring to insure that air entrainment doesn't take place. Also care should be taken to not scrape the side of the bucket which could result in shearing small particles of plastic and possibly clogging the spray nozzle. LEVELCOAT™ should be applied with an airless sprayer in a "cross-hatch" pattern to a total thickness of 15 wet mils utilizing a tip aperture suitable to the flow rating of the spray rig being used, such as a .023 with a sprayer rated at 1 gallon per minute. We recommend using a 3/8" hose. Since LEVELCOAT™ is double screen filtered at the factory, many contractors have found that removing the filters from spray equipment allows a more efficient application. Should "fingering," or spray-fan marks occur during application, we recommend that any or all of the following be performed:**

1. **increase** the pressure of the pump
2. **decrease** the tip aperture and/or
3. **dilute** the **LEVELCOAT™** by up to 1 pint of clean (drinkable) water.

Undiluted, **LEVELCOAT™** will cover approximately 130 square feet per gallon at 15 wet mils. **LEVELCOAT™** can be back rolled if you desire a textured, "stippled" finish. If so we recommend a single-pass from top to bottom with a 1/4" - 1/2" synthetic knap roller. **CAUTION:** Due to the low shrinkage nature of the product, extra attention is necessary to insure the absence of roller marks.

LEVELCOAT™ is also easily sandable, eliminating the problem of overspray clean up.

Should you have any questions or comments regarding **LEVELCOAT™**, please contact us at 1-800-255-6678